

COMORCAP LS

PAINT REMOVER

COMORCAP LS is an organic solvent compound, perfectly stable, formulated to eliminate paints from all surfaces, by spraying or by dipping.

No corrosive effect on metals, particularly on steels and light metal alloys. Can be used on wood. Attacks rubber and some plastic materials.

INTENDED USES

- . Removal of air-dried or stoved paints (glyptal resin and cellulose lacquers, synthetic paints), by dipping the parts in an ordinary steel tank.
- . Take care not to introduce water into the treatment tank. After utilization, close the tank hermetically.

PROPERTIES

| | | |
|-------------------|-------|-------------------------------------|
| . Composition | | halogenated and oxygenated solvents |
| . Appearance | | translucent liquid |
| . Average density | | 1.28 |
| . Odour | | chlorinated solvent |
| . Inflammability | | no flash point at the boiling point |

PRECAUTIONS FOR USE AND STORAGE

COMORCAP LS contains chlorinated solvents; it is to be used in ventilated rooms.

As for all chlorinated solvents, it is advised not to smoke in presence of vapours and to work far away from flames to avoid the formation of harmful products of decomposition.

Store COMORCAP LS far from sun and flames, in a cool place.

The packages may get out of shape during storage; to be opened carefully.

Please read the safety data sheet for further information.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMOR; all data is subject to change as Socomor deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

Veuillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent
socomor@socomor.com

