

DIESTONE

A 8287

Approvals: SAFRAN Group: TURBOMECA (CCT LB 540)

Excellent dissolving action on paints, inks (classical or UV), varnishes or adhesives.

Non-corrosive on metals and few losses by evaporation.

Compatibility with most synthetic resins (epoxy, polyurethane, acrylic...).

Very safe due to the high flash point.

The flash point is stable in time and remains constant throughout the evaporation duration.

USES

Solvent used for cleaning resin application equipment, as a replacement for acetone, MEK or toluene.

Reactivating cleaning solvent for metallic or painted surfaces before painting.

DIRECTIONS FOR USE

DIESTONE A 8287 is suitable for long term dipping or impregnating operations (removal of resins). It can also be applied by means of a brush or a swab.

After cleaning, the application material must be dried thoroughly

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent*

socomor@socomor.com



TECHNICAL CHARACTERISTICS

• Appearance	colourless limpid liquid
• Density	0.89
• Flash point (ISO 2592).....	40°C
• Evaporation rate (NFT 30301).....	0.3

PRECAUTIONS FOR USE AND STORAGE

Because of the degreasing action of the product, it is advised to wear safety gloves during handling. As for all flammable solvents, take the usual safety measures during use and storage.

Please consult the safety data sheet for further information.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMOR ; all data is subject to change as Socomor deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent*

socomor@socomor.com

