

DIESTONE A 8290

CLEANING DILUENT WITH HIGH FLASH POINT

DIESTONE A 8290 is a solvent composition with a controlled volatility, without halogenated hydrocarbons; it is used as a cleaning product.

- Non corrosive on metals. Efficient reactivation and cleaning of epoxy or polyurethane primers.
- Pleasant odour.
- Compatible with epoxy, polyurethane, acrylic paints.

USES

Painting and paint stripping shops, construction and assembly :

- Cleaning of paint systems.
 - Cleaning of paint application equipment (brushes, rollers, spray guns, spray booths, etc...).
- Removal of "washable" temporary protection
- Cleaning of jointing, sealant and glue application equipment
 - Removal of excess quantities, marks and runs of jointing products, sealants and glues.

DIRECTIONS FOR USE

DIESTONE A 8290 can be used as supplied and without dilution at ambient temperature using the following methods:

- by circulation in paint equipment pipes,
- spraying,
- brushing or swabbing.

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent*

socomor@socomor.com



TECHNICAL CHARACTERISTICS

- . Appearance clear liquid
- . Density at 20°C 0.9
- . Flash point (ISO 2592)..... 41°C
- . Halogenated hydrocarbon Content none
- . Odour light

PRECAUTIONS FOR USE AND STORAGE

It is recommended to wear suitable gloves because the strong degreasing action of **DIESTONE A 8290** will de-fat the skin. Avoid breathing or swallowing the product. Wear suitable eye protection when handling or using the product. In the case of contact with skin or eyes, rinse immediately and abundantly with water. If work is continuous, it is recommended to install a vapour extraction system at the emission point.

DIESTONE A 8290 must be used and stored in a sufficiently ventilated place, away from flame and heat sources. The product must be protected and kept in the closed original containers.

Please consult the safety data sheet for further information.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMOR ; all data is subject to change as Socomor deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

Veillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent
socomor@socomor.com

