

DIESTONE D

MULTI-PURPOSE SAFE DILUENT

Approvals:

▪ AIRBUS	AIMS 09.03.000, I.P. DA -62.32 Appendix 1
▪ EUROCOPTER	
▪ SAFRAN Group	TURBOMECA (CCT LA 729 – CCT LB 540)
▪ ARMEE DE L'AIR	STPA (AIR 0011)
▪ AIR FRANCE	FITS 51095
▪ ROLLS ROYCE	oMat 1/257AL
▪ DASSAULT	DGQT 22689

DIESTONE D is a solvent composition with controlled volatility. It is free from halogenated hydrocarbons and used as a cleaning agent. The product provides maximum security, it is absolutely free from any aromatic component harmful to health. It does not contain any teratogenic or carcinogenic components.

Very high solvent power, which gives excellent cleaning and degreasing of metallic surfaces before painting.

Compatible with epoxy, polyurethane, acrylic and nitrocellulose paints and lacquers.

Non-corrosive on metals, including light alloys.

Absolutely free from toluene, xylene and glycol ethyl acetate;

Efficient reactivation and cleaning of epoxy and polyurethane primers.

The flash point is stable in time and remains constant throughout the evaporation period.

Pleasant odour.

Available in liquid form, and in CONTEC presaturated wipes.

USES

Painting and paint stripping shops, construction and assembly:

- Cleaning of paint application equipment (brushes, rollers, spray guns, spray booths, etc...).
- Subsidiary stripper of dry paint films (elimination of polyvinyl primers and nitrocellulose lacquers).
- Suitable for eliminating graffiti, felt-tip, inks, etc...
- Degreasing of epoxy/carbon composites before painting.
- Cleaning of jointing, sealant and glue application equipment
- Removal of excess, marks and runs of jointing products, sealants and glues.

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent*

socomor@socomor.com



DIRECTIONS FOR USE

DIESTONE D is used as supplied without dilution at ambient temperature using the following methods:

- spraying,
- brushing or swabbing,
- by circulation in paint equipment pipes.

TECHNICAL CHARACTERISTICS

- Appearance clear liquid
- Density at 20° C (68°Fh)..... 0.92
- Flash point (ISO 2592)..... 30°C (86°Fh)
- Evaporation rate (NFT 30301)..... 0.5
- Halogenated hydrocarbons..... none

PRECAUTIONS FOR USE AND STORAGE

It is recommended to wear suitable gloves because the strong degreasing action of DIESTONE D will de-fat the skin. Avoid breathing or swallowing the product. Wear suitable eye protection when handling or using the product. In the case of contact with skin or eyes, rinse immediately and abundantly with water. If work is continuous, it is recommended to install a vapour extraction system at the emission point.

DIESTONE D must be used and stored in a sufficiently ventilated place, away from flame and heat sources. The product must be protected and kept in the closed original containers.

Please consult the safety data sheet for further information.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMOR ; all data is subject to change as Socomor deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.

Socomor
Finishing Technologies

Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomor.com

*Veillez consulter notre site Web pour connaître notre correspondant le plus proche
Please consult our Web site to find our nearest correspondent*

socomor@socomor.com

